



# Gold Standard Brushless Loader

The GSL Series Loader\* with standard brushless motor, pendant control and pivot access, boasts a 5-Year Warranty

As brushes wear, the commutator wears creating an increasing gap where dust contamination and motor failure occurs. These factors cause brushes to wear down faster and faster with each change, leading to added maintenance and downtime. Motor manufacturers recommend discarding vacuum loader motors after three brush sets.

## Maintenance-free Brushless Motors Last 4 Times As Long As Motors With Brushes

Long-life motor and no brush changes eliminate maintenance and downtime.

## Double Pivot Access

Loader operates in upright position then pivots and locks in place for easy access.

\*Patent # 8,753,432 and 8,070,844

### Plus

- › 115V/1ph/50-60 Hz operation
- › 15 ft (4.6 m) length of flex hose, lance and hose clamps
- › Dual reinforced polyester disc filter media
- › All material contact points are non-ferrous
- › Dump Valve with integrated demand level switch on standard models
- › Conveying rate up to 1000 lb/hr
- › 5-Year warranty

## Full-featured, Standard Plug-In Pendant Control

Full-featured control is mounted on loader. A 12' cable (standard) puts control at your fingertips, so changing loader parameters is easy.

## MicroBurst Keeps Filters Clean

High intensity MicroBurst blowback air, blasts the whole filter area to remove dust and fines ensuring that the dump throat is clear for proper sealing.

## SureSeal Flapper Valve Avoids Loading Failures

Reliable SS seal surfaces stay aligned and resist wear, while MicroBurst air blast removes residual dust for a tight seal.

— 5 —  
YEAR  
warranty





GSL-19

GSL-12

Remote pendant control

# Application

Brushless Vacuum Motor Lasts 4X Longer with No Brush Changes!



Full-featured control includes load time, no-load alarm, alarm light and silencer as well as proportioning and purging.

## Upright Operating Position





Easy pivot access for clean out



Loader pivots forward from operating position and captive detent pin locks loader in place during operation. Lid pivots back and locks in place for easy access.

## Pivot Position for Easy Access



## Specifications:

Model	Capacity*	Inlet O.D.	Discharge Diameter	A	B	C	D
GSL-12	12 lb	1.5	3	25.20	15.03	31.38	17.44
GSL-19	19 lb	1.5	3	29.20	14.95	34.77	19.40

\*Based on PC pellets @ 38 lb/ft<sup>3</sup>


Pivoting and opening top requires 6" (15.2 cm) for clearance on GSL-19.

Recommended throughput: GSL-19 = up to 1000 lb/hr (450 Kg/hr) GSL-12 = up to 650 lb/hr (295 Kg/hr) based on free flowing virgin pellets through 15' of flex hose.

Exceeding recommended throughputs may result in shortened motor and filter life; however, increased throughputs are possible depending on resin and equivalent feet calculation.

Generally, a central conveying system should be used for higher throughputs.

Maximum conveying distance in addition to 15' hose, can include 30' of horizontal tubing and 1 elbow. Additional vertical travel, bends or flex hose will reduce recommended throughput.




### Mounting Flexibility

Standard mounting hole pattern plus adapter ring allows GSL to replace any Novatec loader as well as competitive models.

10.38" O.D.

9.00" Dia. Bolt Hole Circle

.3125" Dia. Typ. (4 places)




Mounting Patterns



Machine mount flange dimensions 6" x 6"

### Machine Mount Glass for GSLs



Config	Machine Mount Assy P/N*	A (in.)
8 lb	GMM-GSL-8	14.47
12 lb	GMM-GSL-12	18.47
16 lb	GMM-GSL-16	22.47

\* Order separately. Must be assembled in field.

### Options:

**2" Inlet:** (in lieu of 1.5")

**Extended Wear Package:** Recommended when loading abrasive materials - contact factory

**Alternate Glass Size:** 12 lb glass (adds 4" to height) or 16 lb glass (adds 7" to height)

**Retro-fit Kit to convert GSLs into machine mount models:** Kit includes glass, twist-lock plug and photo-eye Alternate Mounting Flange (7" x 7" with 3.5" opening) removes 1.5" from height

### Accessories:

**Replacement Plug-N-Play Control Pendant with 12 ft cable:** (one included with each GSL)

**Replacement 12 ft cable**

**External Proportioning Valve:**

(Includes coupler, wand, hose and clamps.) 1.5" and 2.0" O.D.

**Level Switch, Capacitance, 30mm dia., 2m cable**

**Capacitance Level Switch**

**in lieu of Photo-eye Sensor** (for GSL-MM models)